



■ **DK-WORKER®mini**

Hand-held device for winding cold strips onto pipes.



■ **SPECIAL ADVANTAGES**

Maintains the intended width of the tape overlap.  
 Provides even winding tension.  
 Ideal for small diameter pipes.  
 Minimum installation time - fast insulation work.  
 Ideal for confined spaces.  
 The minimum distance around the pipe is 250 mm.

■ **TECHNOLOGY**

The use of winding devices increases the speed of work and the technological reliability of anticorrosive coatings of pipelines.

■ **AREA OF APPLICATION**



**DK-WORKER®mini** is used for manual winding of cold strips on pipes, pipe elbows and welds.  
 Ideal for insulation with **DK-BUT®** & **DK-BIT®** tapes in widths from 50 mm to 100 mm.

■ **RELATED PRODUCTS**

**Rock Shield DK-PROTEC®** - additional mechanical protection of anticorrosive coatings of gas and oil pipelines from physical damage when laying in difficult soils containing inclusions of stones, pebbles and others.  
**Rock Shield DK-PROTEC®** - protects the pipeline during operation from the effects of stony ground in case of its possible displacement.  
**Rock Shield DK-PROTEC®** - protects insulated piping surfaces during transport and installation.

## ■ PRODUCT PROPERTIES

Properties	Unit	DK-WORKER®mini
Pipe diameter	mm	≥89
Sleeve diameter	mm	41
Belt width	mm	≤100
Roll diameter	mm	≤170
Removing the release tape	---	no
Distance around the pipe, minimum	mm	250

## ■ PACKAGING, STORAGE AND TRANSPORTATION

**Packaging:** polymer / cardboard, packing is not returned after use.

**Storage:** in original packaging, in a dry place without load in a horizontal position, in warehouses, open areas under a canopy, protected from sunlight and atmospheric precipitation. When storing the **DK-WORKER®mini** and transporting it to the work site, store and transport in an upright position. Transportation and storage at a distance of at least 1 m from heat sources.

Shelf life in original packaging is at least 36 months from the date of manufacture.

Storage temperature: ≤ +50°C (+122°F).

**Transportation:** on pallets, in original packaging, by all means of transport.

## ■ Consult with us for specific projects or unique applications

The product information shown here our application recommendations and other product related documents are made for your convenience only. Since many installation factors are beyond our control, the user shall determine the suitability of the products for the intended use and assume all risks and liabilities in connection therewith.

All information contained in this document is to be used as a guide and does not constitute a warranty of specification. The information contained in the document is subject to change without notice.

For this reason, no liability can be accepted for inaccurate advice or any failure to provide advice. The user is responsible for checking the applications of the product and verifying its suitability for the intended use.

This is the original translation of product information from the Polish language.

In case of any discrepancy or any dispute arising on the interpretation of this product information, the Polish text of the respective Polish product information, which is available at [www.dkd-korporation.com](http://www.dkd-korporation.com), shall be decisive.

The legal relationship shall be governed by Polish law.



**INDUSTRIAL CORPORATION**

DKDK INDUSTRIAL CORPORATION  
ul. Grzybowska 87  
00-844 Warszawa, Polska  
tel.: +48 539 980 916  
[info@dkd-korporation.com](mailto:info@dkd-korporation.com)  
[www.dkd-korporation.com](http://www.dkd-korporation.com)

07.2020