

# PRODUCT DATA SHEET

## ORIGINAL **kebu**® Plast Mastic Special



Kebu Plast Mastic Special is a polystyrene ball containing compound based on the proven Kebu Plast Mastic for filling cavities and for levelling surfaces of buried pipe fittings.

The polystyrene balls in Kebu Plast Mastic Special result in a lower density of the compound and thus provide more volume for filling cavities at low weight. In addition, they facilitate the processability of the compound at low temperatures.



### ■ SPECIAL ADVANTAGES

Cold applied mastic  
Based on petrolatum  
Solvent-free  
Easy and fast application

### ■ AREA OF APPLICATION



The Kebu Plast Mastic Special is compatible with factory coatings of PE, PP, epoxy resin, PU and bitumen. It is suitable for the application in void risk areas like gorges, around screws, nuts as well as for gaps between flanges. It can be used for Field Joint Coating, Coating Rehabilitation and Coating Repair.

### ■ FORMS OF DELIVERY

Forms of delivery	Packing	Wigth (kg)
Kebu Plast Mastic Special	Plastic bucket	5
		20

### ■ APPLICATION

The area to be coated must be dry and free of dust and grease. If necessary, dry the surface using a propane torch or use Kebu Priming Paste. There is no need to preheat the area A surface cleanliness of St 2 according to 8501-1 is sufficient for this application. Take Kebu Plast Mastic Special from the packaging, kneading it by hand or with a spatula. It is suitable for the application in void risk areas like gorges, around screws, nuts as well as for gaps between flanges. Subsequent the Kebu Plast Mastic Special needs to be coated by a suitable petrolatum tape, like **Kebu Tape**, **Kebu Petro Tape A303** or **Kebu Tape 90** with the required number of layers.

### ■ PROPERTIES of Kebu Plast Mastic Special

Property	Unit	Typical values
Colour	---	brown
Consistency	---	deformable
Congeaing point	°C	> 60
Operating temperature	°C	≤ 30
Processing temperature	°C	5-30
Saponification number	mg KOH/g	max. 2

## ■ PACKAGING, STORAGE AND TRANSPORTATION

**Packaging:** plastic bag / carton, packing is not returned after use.

**Storage:** in original packaging, in a dry place without load in a horizontal position, in warehouses, open areas under a canopy, protected from sunlight and atmospheric precipitation. When storing the **Kebu Plast Mastic Special** and transporting it to the work site, store and transport in an upright position, no more than six rows - boxes with tape, and three rows - containers with primer. Transportation and storage at a distance of at least 1 m from heat sources. Shelf life in original packaging is  $\geq 24$  months from the date of manufacture.

Storage temperature: from  $-5^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$ .

**Transportation:** on/without pallets, in original packaging, by all means of transport.

## ■ SUITABLE ACCESSORIES

### Kebu Tape

Is a cold applied corrosion protection petrolatum tape.



### Kebu Petro Tape A303

Is a cold applied corrosion protection petrolatum tape, a synthetic fiber fabric as an insert and a laminated PE film.



### Kebu Rockshield PP 500/1000

Additional mechanical protection (non-woven PP) for coated pipes and valves or for buried plastic.



## ■ CONSULT WITH US FOR SPECIFIC PROJECTS OR UNIQUE APPLICATIONS

The product information shown here our application recommendations and other product related documents are made for your convenience only. Since many installation factors are beyond our control, the user shall determine the suitability of the products for the intended use and assume all risks and liabilities in connection therewith.

All information contained in this document is to be used as a guide and does not constitute a warranty of specification. The information contained in the document is subject to change without notice.

For this reason, no liability can be accepted for inaccurate advice or any failure to provide advice. The user is responsible for checking the applications of the product and verifying its suitability for the intended use.

This is the original translation of product information from the english language.

In case of any discrepancy or any dispute arising on the interpretation of this product information, the english text of the respective english product information, which is available at [www.dkd-korporation.com](http://www.dkd-korporation.com), shall be decisive.

The legal relationship shall be governed by Polish law.

Rev.:01.06.2023



INDUSTRIAL CORPORATION

DKDK INDUSTRIAL CORPORATION  
ul. Grzybowska 87  
00-844 Warszawa, Polska  
tel.: +48 539 980 916  
[info@dkdk-corporation.com](mailto:info@dkdk-corporation.com)  
[www.dkd-korporation.com](http://www.dkd-korporation.com)