

PRODUCT DATA SHEET

ORIGINAL **kebu**® mat Wrapping devices

The KEBUmat wrapping device is a manual tool for the application of Kebutyl tape systems and the Kebulen-Tape B 80-C. The tapes are applied with ease in compliance with the required overlap and application tension. KEBUmat wrapping devices are built for extreme side conditions and a fast-working pace. The different types of the KEBUmat wrapping device are perfectly suited for straight and bended pipes.



Kebumat "Mini"

The KEBUmat "Mini" is specifically designed for the tape application at limited space conditions. It's suitable for pipes with a small nominal size DN 40.



Kebumat "ST"

The KEBUmat "ST" is suitable for a variety of applications. It facilitates and accelerates the coating of straight pipes from DN 80 and pipe bends from DN 100.



Kebumat "GR"

The KEBUmat "GR" allows the use of larger rolls for pipes up to DN 1400. The tapes have a maximum width of 150 mm and a roll diameter of 300 mm.

Type	Material support [mm]	Tape width [mm]	Roll diameter [mm]	Nominal size DN	Minimal working height [mm]
"Mini"	41	max 100	max 100	≥ 40	200
"ST"	41	max 100	max 160	≥ 80 pipe bends ≥ 100	300
"GR"	76	max 150	max 300	≥ 300	400

■ Additional accessories on demand, for example an extension arm and wrapping cage for KEBUmat "GR"

■ PACKAGING, STORAGE AND TRANSPORTATION

Packaging: plastic bag / carton, packing is not returned after use.

Storage: in original packaging, in a dry place without load in a horizontal position, in warehouses, open areas under a canopy, protected from sunlight and atmospheric precipitation. When storing the **Kebumat** and transporting it to the work site, store and transport in an upright position. Transportation and storage at a distance of at least 1 m from heat sources.

Shelf life in original packaging is ≥ 24 months from the date of manufacture.

Storage temperature: from -5°C to $+50^{\circ}\text{C}$.

Transportation: on/without pallets, in original packaging, by all means of transport.

■ RELATED PRODUCTS

Kebutyl-System C 50-C

Is a cold applied two-tape system according to EN 12068 (class C 50), DIN 30672 (class C 50) and ISO 21809-3 type 12A-1 (Tmax 50°C)



Kebulen Band B 80-C

Is a three-layer corrosion protection tape according to DIN EN 12068, DIN 30672 and ISO 21809-3



Kebu Rockshield PP 500/1000

Additional mechanical protection (non-woven PP) for coated pipes and valves or for buried plastic.



■ CONSULT WITH US FOR SPECIFIC PROJECTS OR UNIQUE OFFERINGS

The product information shown here our application recommendations and other product related documents are made for your convenience only. Since many installation factors are beyond our control, the user shall determine the suitability of the products for the intended use and assume all risks and liabilities in connection therewith.

All information contained in this document is to be used as a guide and does not constitute a warranty of specification. The information contained in the document is subject to change without notice.

For this reason, no liability can be accepted for inaccurate advice or any failure to provide advice. The user is responsible for checking the applications of the product and verifying its suitability for the intended use.

This is the original translation of product information from the english language.

In case of any discrepancy or any dispute arising on the interpretation of this product information, the english text of the respective english product information, which is available at www.dkd-korporation.com, shall be decisive.

The legal relationship shall be governed by Polish law.

Rev.:01.06.2023



INDUSTRIAL CORPORATION

DKDK INDUSTRIAL CORPORATION
ul. Grzybowska 87
00-844 Warszawa, Polska
tel.: +48 539 980 916
info@dkdk-corporation.com
www.dkd-korporation.com