

PRODUCT DATA SHEET

ORIGINAL kebu® Kebulen patches C 50



Hot applied defect patch meeting DIN EN 12068 and DIN 30 672, load class C, continuous operating temperature up to 50°C.



■ STRUCTURE

Patch set consisting of:
 Patches made of modified PE, 140 mm x 170 mm,
 Kebutyl putty as filling material 40 mm x 40 mm x 5 mm
 Emery cloth P 80, 25 mm x 280 mm

■ FORMS OF DELIVERY

Length of roll [m]	Width of roll [mm]
15	150
15	300
30	150

■ PACKAGING, STORAGE AND TRANSPORTATION

Packaging: carton, packing is not returned after use.

Storage: in original packaging, in a dry place without load in a horizontal position, in warehouses, open areas under a canopy, protected from sunlight and atmospheric precipitation.

Shelf life in original packaging is ≥24 months from the date of manufacture.

Storage temperature: from -5°C to +40°C.

Transportation: on/without pallets, in original packaging, by all means of transport.

■ CONSULT WITH US FOR SPECIFIC PROJECTS OR UNIQUE OFFERINGS

Since many installation factors are beyond our control, the user shall determine the suitability of the products for the intended use and assume all risks and liabilities in connection therewith.

All information contained in this document is to be used as a guide and does not constitute a warranty of specification.

The information contained in the document is subject to change without notice.

For this reason, no liability can be accepted for inaccurate advice or any failure to provide advice.

The user is responsible for checking the applications of the product and verifying its suitability for the intended use.

This is the original translation of product information from the english language.

In case of any discrepancy or any dispute arising on the interpretation of this product information, the english text of the respective english product information, which is available at www.dkd-korporation.com, shall be decisive.

The legal relationship shall be governed by Polish law.